

Product Details NST-IPM31335-AD



Model No.		NST-IPM31335-AD
Camera Type		Dome IP Camera
System		Embedded RTOS design
Camera	Effective Pixels	4.0 Mega Pixels
		Main stream:4.0MP(2560*1440)
		Sub stream:704*576
	Frames Rates	PAL:25fps(2560*1440)
		NTSC:30fps(2592H*1944)
	Image Sensor	1/2.7" SC401AI CMOS Sensor
	DSP	Dual core 32-bit DSP
		(GK7205V200)
	Min. Illumination	Color 0.01Lux@F1.2
		B/W 0.001 Lux@F1.2
Adjust Parameters	WDR,BLC,DNR,AE,AGC,D&N,Mirror,Flip,etc.	
Video	Compression	H.265 Main profile
	Stream	support dual stream,AVI format
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable
	Frame Rates	support 1~30fps adjust
Audio	Audio	built in audio
	Compression	G.711 compression
Alarm	Types	Motion Detection, Video Blind , Video Loss
Network	WEB Browser	Support WEB remote config(IE, Safari, Google Chrome, Firefox etc.)
	Smart Phone	mobile remote Monitoring (iPhone,Android,Windows Mobile,BlackBerry,Symbian)
	CMS Software	Uniform CMS Software(multiple devices management system)
	Cloud P2P	www.xmeye.net,XMEYE platform and other program,Offer SDK
	Network	1 * RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP
	ONVIF	Support
	POE	Support
General	Language	20 kinds of languages such as English, Finnish, French, German, Greek,Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, S-Chinese, T-Chinese and Turkish
	IR Cut Filter	Set of double light switch IR-CUT filter
	Lens Mount	Varifocal Lens 2.8-12mm
	Infrared Luminary	30pcsF5 IR Leds
	Infrared Wavelength	850 nm
	Illuminate Distance	More than 30M
	Waterproof	IP67
	Vandalproof	IK10
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)
	Supplied Voltage	DC12V/PoE(802.3af/820.3at)
	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA
	Working Enviroment	-10℃~+60℃, 10%~90% (Built in Heater being optional added for enviroment lower than -20°)
	Weight	1.0kg

